



- **Standard SIP/VoIP phone**
- **Robust housing, constructed of stainless steel**
- **Vandal resistant metal button**
- **Rugged keypad with 12-key**
- **Hands free operation**
- **In wall mounted, simple installation**
- **Weather proof protection: up to IP65**
- **External power supply or PoE (SIP)**
- **RJ45 Port for SIP connection**
- **4 X Tamper proof screws for mounting**
- **CE, FCC, RoHS, ISO9001 compliant**

The Hands free Telephone is designed to meet the needs of client who experience loss through vandalism. Ideal for clean room, sterile areas, parking lots, prisons, railway/metro platforms, hospitals, police stations, ATM machines, stadiums, outside building etc.

Housed in cold rolled steel box and manufactured to a high standard, these telephones offer increased resistance to vandalism, and ensure that the primary function of communications is maintained at all times.

Extremely easy to install. The cable entrance is on the back of the phone to prevent from artificial damage, while the keypad is weather and vandal resistant.

SIP-VoIP TECHNICAL SPECIFICATIONS

Adapter Input:

100-240VAC 50~60Hz Output:5V/1A

Port:

WAN: 10/100Base- T RJ-45 for LAN, Auto MDIX

LAN: 10/100Base- T RJ-45 for PC, Auto MDIX

Power Consumption:

Idle:1.5W/ Active:1.8W

Main Chip:

Broadcom

Voice Features

- Support 2 lines SIP, SIP 2.0 (RFC3261)
- Codec: G.711A/u, G.7231 high/low, G.729, G.722,G.726
- Echo cancellation: Support G.168 and hand-free can support 96ms
- Supports full duplex.
- SIP support SIP domain,SIP authentication(none, basic,MD5),DNS name of server, peer to peer
- SIP support 2 servers, user can through each server to calling in and out

Network Features

- WAN/LAN: support Bridge mode
- Support PPPoE for xDSL
- Support VLAN
- Support Stun penetration
- Support DHCP get IP on WAN port

TECHNICAL SPECIFICATIONS

Casing Material

Stainless steel body

Handset Material

No handset

Keypad

Rugged metal keypad

Hook switch

No hook switch

Push button

Stainless steel button with IP65 rate

Temperature

Operating: -30°C to +65°C

Storing: -40°C to +75°C

Weather Resistance

Up to IP65

Ringing Tone

Shrill warble tone 80 dBA @ 1 metre typical



M.T.B.F.

Calculated to have an M.T.B.F. in excess of 50,000 hours using

Weight

Up to 2.5 kg depending on option

DIMENSIONS



(Measured in mm)

APPROVALS



This mark indicates compliance with the: Radio & Telecommunications Terminal Equipment Directive 2004/108/EC



This mark indicates compliance with the: FCC Part 15 Subpart B Class B

PACKAGE

Unit size: 240 * 150 * 32 (mm)

Carton size: 340 * 235 * 165 (mm)

Packaging materials: pearl cotton, carton

Gross weight: 3 KG

Net weight: 2 KG